



- NOTES**
1. MINIMUM CONCRETE STRENGTH AT 28 DAYS- 20MPa. (2000psi)
 2. RESIDENTIAL SLAB & FOOTINGS TO AS.2870
 3. ALL BUILDING REQUIREMENTS TO AUSTRALIAN BUILDING CODES & REGULATIONS
 4. FOOTING & SLAB DETAILS TO ENGINEERS DESIGN & SPECIFICATIONS.
 5. THESE DETAILS TO BE READ IN CONJUNCTION WITH DESIGN & CONSTRUCTION MANUAL.

SLAB DESIGN IS INDICATIVE ONLY
 PLEASE REFER ALSO TO:-
 (1) SOIL TEST
 (2) STRUCTURAL CERTIFICATION.

SIGNATURE OF CERTIFYING
 STRUCTURAL ENGINEER :-



FORCE 10 INTERNATIONAL PTY LTD
 63 FACTORY ROAD, OXLEY
 QUEENSLAND, AUSTRALIA 4075
 PH. +61 7 33795200 FX. +61 7 33795211
 email:- reception@force10.com.au

REV	BY	DATE	REV	BY	DATE
1	KDA	14-08-93			
2	AUC	05-09-96			
3	AUC	11-03-99			
4	AUC	30-07-03			

DRAWN BY : K.D.A
DATE : 05 / 05 / 98
CHECKED :
A3 SCALE : NTS.

DETAIL DRAWING TITLE :
 TYPICAL SLAB DETAILS
 GENERAL SPECS ONLY

DETAIL DRAWING NUMBER : DT 000
REVISION : 4

THE FORCE 10 ENGINEERED BUILDING SYSTEM IS PROTECTED BY WORLD-WIDE PATENTS. THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN PART OR WHOLE WITHOUT WRITTEN CONSENT FROM FORCE 10.