



COLORBOND RIDGE CAPPING
 BINDERS TO BOTTOM CHORD SAME AS PURLINS

ROOFING TO MANUFACTURERS SPECIFICATION FIXED TO TOP HAT PURLIN
 PURLINS 65x40mm SPACED TO SUIT TRUSS SIZE MAT'L. - 1.2mm G300/1.6mm G300

STEEL FRAMED ROOF TRUSS TO MANUFACTURERS SPECIFICATIONS AT 20° PITCH (SEE DT007)

COLORBOND FASCIA AND GUTTER

EAVES LINING 6mm F/C SHEET STD. SIZES:- 90\300\600\900mm

42x19 TIMBER EAVES BATTEN

STEEL FRAMED PANEL 6mm F/C SHEET BOTH SIDES POLYURETHANE FILLED CAVITY (SEE DT002, DT003, DT004, DT005 & DT006)

FLASHING TO WALL AND FLOOR 0.6mm STAINLESS STEEL

BEARER FLASHING 0.8mm ZINCALUME

90mm PLASTER CORNICE
 10mm GYPROCK TO CEILING

68x12mm BULLNOSE TIMBER SKIRTING

22mm PARTICLE BOARD OR 18mm PLYWOOD FLOORING

STEEL FLOOR SYSTEM BEARERS AND JOISTS 75x75x2.3 OR 5.0mm GALVANIZED SHS

STANDARD FOOTING DETAIL (SEE DT001 OR AS PER SOIL TEST)

CEILING BATTENS - 25mm SPACED AT 500mm CENTRES

FACE FIXED WINDOWS

GROUND
 FLOOR
 600-900
 22 OR 18
 OVER 900, BRACING MAY REQ'D. OVER 1800, 5.0mm WALL REQ'D. (SEE DT001 & DT015)

FORCE 10

"BUILDING SOLUTIONS FOR THE WORLD"
 QUALITY APPROVED TO AS/NZS ISO9001

FORCE 10 INTERNATIONAL PTY LTD
 63 FACTORY ROAD, OXLEY
 QUEENSLAND, AUSTRALIA 4075
 PH. +61 7 33795200 FX. +61 7 33795211
 email:- reception@force10.com.au

THE FORCE 10 ENGINEERED BUILDING SYSTEM IS PROTECTED BY WORLD-WIDE PATENTS. THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN PART OR WHOLE WITHOUT WRITTEN CONSENT FROM FORCE 10.

REV	BY	DATE	REV	BY	DATE
2	A.J.C.	-			
1	A.J.C.	-			

DRAWING REVISIONS

DRAWN BY : A.J.C.
DATE : 03/07/95
CHECKED :
A3 SCALE : N.T.S.

DETAIL DRAWING TITLE :
TYPICAL SECTION THROUGH STANDARD HOUSE

DETAIL DRAWING NUMBER : DT 010
REVISION : 2

SIGNATURE OF CERTIFYING STRUCTURAL ENGINEER :-
